

DECLARATION OF PERFORMANCE No DHINTRA-SM-SLIM-G-10-2020

| Unique identification code of the product-typ | e | DEFRO HOME INTRA SM SLIM G ref. KOM-IN-SM-SLIM-G | | |
|-----------------------------------------------|-------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|--|
| Intended use | | Room heater fired with solid fuel in the buildings | | |
| Manufacturer | | DEFRO Spółka z ograniczoną odpowiedzialnością Spółka komandytowa 00-403 Warszawa, ul. Solec 24/253 Manufacturing plant: 26-067 Strawczyn, Ruda Strawczyńska 103A | | |
| System/s of AVCP | | System 3 | | |
| Harmonised standard | | PN-EN 13229:2002, PN-EN 13229:2002/A1:2005, PN-EN 13229:2002/A2:2006, Commission Regulation (EU) 2015/1185 | | |
| European Assessment Document | | Institute of Power Engineering - Research Institute, Notified Body no. 1452 has made an assessment of performance based on the tests in system 3 and had issued test report no. 152/19-LG | | |
| | DECLAREI | D PERFORMANCE | S | |
| Essential characteristics | | Performance | Technical specification | |
| CO emission in combustion products | 0,095 % (13% O ₂) 1185 mg/m³ (13% O ₂) | | PN-EN 13229:2002 PN-EN 13229:2002/A1:2005 PN-EN 13229:2002/A2:2006 | |
| OGC emission in combustion products | 52 mg/m ³ | | Commission Regulation (EU) 2015/1185 | |
| NOx emission in combustion products | 116 mg/m ³ | | Commission Regulation (EU) 2015/1185 | |
| PM emission in combustion products | 13 mg/m ³ | | Commission Regulation (EU) 2015/1185 | |
| Temperature of external surfaces | 4.2, 4.13, 5.2, 5.3, 5.6, 5.10 | | PN-EN 13229:2002 PN-EN 13229:2002/A1:2005 PN-EN 13229:2002/A2:2006 | |
| Electric safety | 5.9 | | PN-EN 13229:2002 PN-EN 13229:2002/A1:2005 PN-EN 13229:2002/A2:2006 | |
| Max. permissible work pressure | not applicable | | PN-EN 13229:2002 PN-EN 13229:2002/A1:2005 PN-EN 13229:2002/A2:2006 | |
| Mechanical strength | No leaks and permanent deformations | | PN-EN 13229:2002 PN-EN 13229:2002/A1:2005 PN-EN 13229:2002/A2:2006 | |
| Flue gases temperature | 224 °C | | PN-EN 13229:2002 PN-EN 13229:2002/A1:2005 PN-EN 13229:2002/A2:2006 | |
| Thermal power/Energy efficiency | 6,7 kW / 82,7 % | | PN-EN 13229:2002 PN-EN 13229:2002/A1:2005 PN-EN 13229:2002/A2:2006 | |
| Primary fuel | hard wood fuel | | Operating manual | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

| Signed for | or and on | hehalf of th | e manufacture | hv. |
|------------|-----------|--------------|---------------|-----|
| | | | | |

Robert Dziubeła – CEO

Warszawa, dn. 15.10.2020 r.

(place and date of issue)

(name and position)

(signature)